

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	BioBlend® XD 26150 BioPolymer
Common Names	BioBlend® XD
Product Use	Resin for extrusion
Manufacturer	BioLogiQ Inc. <i>Headquarters</i> 2400 E 25 th St. Idaho Falls, ID 83404 <i>Manufacturing</i> 835 NE Main St. Blackfoot, ID 83221
Emergency Number	1-208-357-9650

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification and Label Elements

Category	Combustible Dust (OSHA Defined)
Label Content	
Pictogram	Not required
Signal word	WARNING
Hazardous warnings	May form combustible dust concentrations in air.
Hazardous prevention measures	Not required

Other Hazards

Physical / Chemical Hazards

Combustible Dust	If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
------------------	--

Health Hazards

Eye	H320: Causes eye irritation. Particles may cause mechanical irritation.
Skin Contact	H316: Causes skin irritation. Only when hot.
Inhalation	Low order of toxicity.

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

Ingestion	No hazard in normal industrial use.		
Environmental Hazards	No significant hazard		
NFPA Hazard ID	Health: 1	Flammability: 1	Reactivity: 0
HMIS Hazard ID	Health: 1	Flammability: 1	Reactivity: 0

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Name	CAS #	Concentration	GHS Hazard Codes
NuPlastiQ® GP BioPolymer		-	N/A
Styrene, 1,3-butadiene copolymer	9003-55-8	-	N/A
White mineral oil (petroleum)	8042-47-5	< 1.5%	N/A
Adhesive Resin		< 10%	N/A

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provision of paragraph (i).

SECTION 4. FIRST-AID MEASURES

Eye Contact	Flush eyes with large amounts of water until irritation stops. Seek medical attention if irritation persists.
Skin Contact	Wash with soap and water. For hot product: immediately immerse in or flush affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.
Inhalation	Remove to fresh air.
Ingestion	Not a probable route of exposure. However, in case of accidental ingestion, call a physician.

SECTION 5. FIREFIGHTING MEASURES

Extinguishing Media	Dry chemical; CO ₂ ; Water fog; Foam
Unsuitable Extinguishing Media	No applicable data available.
Specific Hazards	Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

Protective Equipment	ignition source is a potential dust explosion hazard. Do not permit dust to accumulate.
Decomposition products	Self-contained breathing apparatus.
Flammability Properties	Flammable hydrocarbons, incomplete combustion products, water vapor, carbon dioxide (CO ₂), carbon monoxide (CO), aldehydes, ketones, styrene, toluene, alcohols, smoke, and other toxic fumes are possible.
Flash Point	No data
Flammability Limits	LEL: N/D UEL: N/D
Autoignition Temperature	N/A

SECTION 6. ACCIDENTAL RELEASE MEASURES

Safeguards	Avoid the generation or accumulation of dust in the air. Good housekeeping practices should be used to avoid dust build up.
Spill Clean	Spilled material is a slipping hazard on hard surfaces. Sweep or scoop up pellets and remove. Spills of fine material should be cleaned using gentle sweeping or vacuuming. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.
Environmental Precautions	Do not discharge to streams, ponds, lakes or sewers.
Disposal Method	In accordance with existing local/state/federal regulations.

SECTION 7. HANDLING AND STORAGE

Handling	Minimize dust generation and accumulation. Institute routine housecleaning to ensure dust does not accumulate on surfaces. Pneumatic conveying and other mechanical handling operations can generate combustible dust. Avoid significant deposits of material which may become airborne and form combustible dust clouds. Handling and processing operations should be conducted in accordance with best practices (e.g. NFPA-654).
Loading/Unloading Temperature	[Ambient]
Transport Temperature	[Ambient]
Transport Pressure	[Ambient]

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

Storage	Store in cool dry place with adequate ventilation. Do not store near heating source.
Storage Temperature	[Ambient]
Storage Pressure	[Ambient]
Suitable Containers/Packing	Bulk Containers, Bags. Store sealed to prevent moisture absorption and decomposition.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limit Values for materials that can be formed when handling this product When hot processing this material, use local and/or general exhaust ventilation to maintain the concentration of vapors and fumes below exposure limits. Local exhaust ventilation is preferred. Use static controls. Static charges can cause explosions in solvent and dust laden atmospheres. Follow processing recommendations on the product data sheet.

For dusty conditions, OSHA recommends for particulates not otherwise regulated an 8-hour TWA of 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction); ACGIH recommends for insoluble and poorly soluble particles not otherwise specified an 8-hour TWA of 10 mg/m³ (inhalable particles), 3 mg/m³ (respirable particles).

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Under recommended processing conditions, this material has been shown to emit elevated concentrations of glycerol mist (CAS 56-81-5). This may cause smoke and possible odor during processing. OSHA does not list Glycerol mist as a hazardous material with specific exposure limits.

Engineering Controls The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Processors of this product should insure that adequate ventilation is provided to control and minimize exposure. Dust control equipment, exhaust ventilation, and material transport systems involved in handling of this product should be designed and maintained to minimize dust generation and accumulation.

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

Personal Protection

Hand Protection	If product is hot, thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, a long sleeve shirt or gauntlet style gloves is recommended.
Eye Protection	If contact with hot material is likely, safety glasses with side shields are recommended.
Skin and Body Protection	If there is a potential for contact with hot product, thermally protective clothing and footwear is recommended.
Respiratory Protection	If engineering controls do not maintain acceptable airborne contaminate levels, an approved respirator may be appropriate. Typical type: Particulate air-purifying respirator approved for dust / oil mist is recommended.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

General Information / Appearance

Physical State	Solid
Form	Resin Pellets
Type	Mixture
Color	Opaque, off-white to tan
Odor	N/D
Odor Threshold	No data available

Important Health, Safety, and Environmental Information

Relative Density	N/A
pH as is	N/A
pH in 1% Solution	N/A
Boiling Point	N/A
Partition Coefficient	N/A
Specific Gravity	N/D
Evaporation Rate	N/A
Vapor Pressure (mm Hg)	N/A
Vapor Density	N/A
Volatiles	N/A
Volatile Organic Compounds	N/A
Auto ignition Temperature	N/A
Flammability (solid, gas)	May form combustible dust concentrations in air.

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

Flash Point	N/D
Upper Explosion Limit	N/D
Lower Explosion Limit	N/D
Decomposition Temperature	N/D
Oxidizing Properties	N/A
Viscosity	N/A
Other Information	
Freezing Point	N/A
Melting Temperature	N/A
Molecular Weight	>10,000
Solubility in Water	Low

SECTION 10. STABILITY AND REACTIVITY

Reactivity	0 = Insignificant
Stability	Material is stable under normal conditions.
Conditions to Avoid	Avoid elevated temperatures for prolonged periods of time
Materials to Avoid	Strong oxidizers
Hazardous Decomposition Products	This product does not undergo spontaneous decomposition. Exposure to high temperatures may cause decomposition. Possible decomposition products include: Carbon monoxide, Organic acids, Aldehydes, Alcohols, Acrolein, zinc oxides, Acetic acid, Maleic anhydride, Formaldehyde, acetaldehydes , Vinyl acetate

SECTION 11. TOXICOLOGICAL INFORMATION

Product Toxicology	
Oral Toxicity	N/D
Dermal Toxicity	Typical for this family of materials. Estimated LD50, Rabbit > 2,000 mg/kg
Inhalation Toxicity	N/D
Eye Irritation	Solid or dust may cause irritation or corneal injury due to mechanical action. Elevated temperatures may

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.

Chronic (Long-Term) Effects of Exposure

Route of Entry	Eye, skin, inhalation, ingestion
Effects of chronic exposure	N/D
Target Organs	N/D
Special Health Effects	N/D

Other Information

Dust	May be irritating to the eyes and respiratory tract.
Additives	Additives are encapsulated in the product and are not expected to be released under normal processing conditions of foreseeable emergency.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Data for Component: Styrene, 1,3-butadiene copolymer (9003-55-8)	Not expected to be acutely toxic to aquatic organisms. Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).
--	---

Data for Component: White mineral oil (petroleum) (8042-47-5)	Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
---	--

Fish Acute & Prolonged Toxicity

LC50, Lepomis macrochirus (Bluegill sunfish), static test, 96 h, > 10,000 mg/l
LL50, Oncorhynchus mykiss (rainbow trout), static test, 96 h, > 100 mg/l
LL50, Leuciscus idus (Golden orfe), static test, 96 h, > 10,000 mg/l

Aquatic Invertebrate Acute Toxicity

LL50, Daphnia magna (Water flea), static test, , , > 100 mg/l

Persistence and Biodegradability	N/D
----------------------------------	-----

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

Bioaccumulative Potential

Data for Component: White mineral oil (petroleum)(8042-47-5) Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Bioconcentration Factor (BCF): 1,900; Fish; Estimated.

Mobility In Soil

N/D

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Recommendations

Waste Disposal Methods: In accordance with existing federal/state/local environmental regulations.

Empty Containers: Empty container may contain product residue; follow SDS and label warnings even after containers have been emptied.

SECTION 14. TRANSPORT INFORMATION

Land (DOT) Not regulated for Land Transport
Sea (IMDG) Not regulator for Sea Transport
Air (IATA) Not regulated for Air Transport

SECTION 15. REGULATORY INFORMATION

U.S. Regulations

Osha Hazard Communication Standard: This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200 due to the combustible dust hazard.

TSCA In compliance with TSCA Inventory requirements for commercial purposes.

SARA (311/312) Reportable GHS Hazard Classes: Combustible Dust

SARA 313 Regulated Chemical(s) Vinyl Acetate

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
 Product No: BioBlend® XD 26150
 Revision Date: 25 February 2019

CWA / OPA: Plastic pellets are defined by the US EPA under the Clean Water Act (40CFR122.26) as a "significant material" which requires any industrial plant that may expose pellets to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other Clean Water Act violations. Pellets found in storm water runoff are subject to EPA regulations with the potential for substantial fines and penalties.

The following ingredients are cited on the lists below

Chemical Name	CAS Number	List Citations
Styrene, 1,3-butadiene copolymer	9003-55-8	2, 5, 6, 7
White mineral oil (petroleum) < 1.5%	8042-47-5	2, 5, 7, 8
Ethylbenzene* =< 150 PPM	100-41-4	1, 2, 3, 4, 5, 6, 7, 8
Styrene** =< 375 PPM	100-42-5	1, 2, 3, 4, 5, 6, 7, 8
Vinyl Acetate	108-05-4	2, 4, 5, 6, 7, 8, 9

Regulatory Lists Searched

1 = OSHA Z	2 = TSCA	3 = CA P65
4 = CA RTK	5 = Canadian DSL	6 = Japanese ENCS
7 = IECSC	8 = PA Right to Know Act and/or Hazardous Substance List	9 = NJ Hazardous Substance List

*In March 2008, the Office of Environmental Health Hazard Assessment's (OEHHA) Proposition 65 Department proposed an NSRL of 54 µg/day (inhalation) for ethylbenzene.

**In April 2016, the Office of Environmental Health Hazard Assessment's (OEHHA) Proposition 65 Department proposed an NSRL of 27 µg/day for styrene.

SECTION 16. OTHER INFORMATION

Modified: 25 February 2019 Updated naming from NuPlastiQ® XD to BioBlend® XD.
 Created: 18 April 2018 Initial version

N/D = Not determined, N/A = Not applicable

SAFETY DATA SHEET



Product Name: BioBlend® XD 26150 BioPolymer
Product No: BioBlend® XD 26150
Revision Date: 25 February 2019

Key to the H-Codes contained in Section 2 or 3 of this document (for information only)

H316: Causes mild skin irritation

H320: Causes eye irritation. Particles may cause mechanical irritation.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance to safe handling, use, processing storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.